



PAX A950

PCI PTS Security Policy

[V1.01]

PAX Computer Technology (Shenzhen) Co.,Ltd.

Contents

1	Purpose	1
2	General Description.....	1
2.1	Product Model Name and Appearance.....	1
2.2	Product Type	4
2.3	Product Identification	5
2.3.1	Hardware Version	5
2.3.2	Software Version.....	7
3	Installation and User Guidance	8
3.1	Initial Inspection.....	8
3.2	Installation.....	8
3.3	Environmental Conditions.....	8
3.4	Configuration Settings.....	9
3.5	Periodic Inspection and Maintenance	9
3.6	Roles and Responsibilities	10
3.7	Passwords and Certificates.....	11
3.8	Decommissioning.....	11
4	Hardware Security.....	11
4.1	Tamper Response	11
4.2	Privacy Shield	12
5	Software Security	14
5.1	Self-test.....	14
5.1.1	24-hour Restart Scheme	14
5.1.2	Scheduled Restart Scheme	14
5.2	Patching and Updating	14
5.3	Software Signing/Authentication	15
5.4	Software Development Guidance.....	15
5.5	Account Data Protection	15
6	Key Management	17

6.1	Algorithms Supported	17
6.2	Key Management Methods	17
6.3	Key Table	18
6.4	Key Loading	19
6.5	Key Replacement	19
7	Communications and Security Protocols	20
7.1	Communication Interfaces	20
7.2	Communication Protocols and Services.....	20
7.3	Bluetooth Security Guidance	21
	Appendix	22
	Acronyms	22
	References	22

1 Purpose

This document is intended to provide guidance for users on how to use the device in a secure manner, including information on key-management responsibilities, administrative responsibilities, device functionality, identification and environmental requirements.

Any deviation from the approved use of the device will invalidate the PCI PTS POI v7.0 approval.

2 General Description

2.1 Product Model Name and Appearance

Figure 1 shows the appearance of the PAX A950.

The product model name is visible both on the front of the device and on the label on the backside of the device. The product name shall not be covered by a sticker or modified in any way.









Figure 1 PAX A950 Appearance




Figure 2 PAX A950 Label

2.2 Product Type

The device is approved as a handheld PED product under PCI PTS POI v7.0 requirements, and it is designed to process online and offline financial transactions in an attended environment.

It provides display, touch screen (for PIN Entry), contact IC card reader (ICCR), contactless IC card reader, magnetic stripe reader (MSR), camera, SAM card slot, SD card, printer, fingerprint, cellular (SIM, eSIM), speaker, buzzer, Wi-Fi, Ethernet, Bluetooth® wireless technology, BLE Beacons, GPS, USB communications and a power interface. Camera, fingerprint and microphone are not used for biometric identification.

Use of any method not listed in the policy will invalidate the PCI PTS POI approval of the device.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by PAX Technology Limited is under license. Other trademarks and trade names are those of their respective owners.

2.3 Product Identification

2.3.1 Hardware Version

Hardware Version:

A950-0xx-Rx7-0xxx

A950-0xx-Rx7-1xxx

A950-0xx-Rx7-2xxx

A950-0xx-Rx7-3xxx

A950-0xx-Rx7-4xxx

The “x” is non-security related variables.

- The 7th, 8th "x" indicate the communication method supported by the device.
- The 11th "x" represents memory capacity.
- The 15th "x" represents the different custom code.
- The 16th "x" represents the different packaging materials.
- The 17th "x" represents the different power cable.

The product hardware version is visible on the label on the backside of the device (See Figure 3). The label shall not be removed, modified or covered in any way.






Figure 3 Hardware Identification

2.3.2 Software Version

Firmware Version:

27.00.xx xxxxx

The seven “x” on the right side represent non-security related changes, such as system UI changes, functional bug fixes, driver updates, etc.

The version information can be retrieved by performing the operations below.

1. Power on the device.
2. After system initialization and automatic self-test, the main screen appears.
3. Find and click the "Settings" icon to enter the settings menu.
4. Find and click "System" to enter the system menu.
5. Find and click the “About device” menu, then select and enter the “SECURITY VERSION” menu. The security version information about the device will appear as follows, including:

- Firmware Version (shown as “Firmware #”)
- Hardware Version (same as the label on the back of the device)



Figure 4: Version Information Example

Serial Number:

1. Return to the “About device” menu.
2. Find and enter the “Model & hardware” menu, the serial number (shown as ‘Serial number’ and is the same as the label at the backside of device) is displayed.

3 Installation and User Guidance

3.1 Initial Inspection

In order to make sure the product received is exactly the same as specified, the acquirer or merchant must check the product according to the tips below.

- Only purchase devices from PAX or PAX authorized resellers.
- Check the integrity and correctness of the devices.
 - Check that the PAX logo labels on the outside of the master carton are complete and non-defective.
 - Check that the serial number labels listed on the master carton are non-defective.
 - Check that the serial number on each device is the same as the one shown on the packing box and master carton.
 - Check that the contents in each packing box match the packing list.
 - Package style: one machine inside a printed box, then boxed into a master carton.
 - Check if there is a tampered message prompt after power up.

Please refer to [3] for more details. If additional technical information is needed, please contact our local support team.

3.2 Installation

The terminal must be used in an attended environment.

The terminal should be kept away from the direct sunlight, high temperature, high humidity or dusty places.

The wireless terminal should be kept away from the complex environment of electromagnetic radiation.

The terminal should be checked according to section 3.5 when installed.

3.3 Environmental Conditions

The environmental conditions for operating the device are specified below.

- Working Environment:

- Temperature: $-10^{\circ}\text{C}\sim+50^{\circ}\text{C}$ ($14^{\circ}\text{F}\sim122^{\circ}\text{F}$)
- R.H.: 5%~95% (Non-condensing)
- Storage Environment:
 - Temperature: $-20^{\circ}\text{C}\sim70^{\circ}\text{C}$ ($-4^{\circ}\text{F}\sim158^{\circ}\text{F}$)
 - R.H.: 5%~95% (Non-condensing)
- Power Supply:
 - DC 5.0V / 2.0A
- Environmental Protection Features:
 - Temperature sensor: $-40\pm 10^{\circ}\text{C}\sim105\pm 15^{\circ}\text{C}$ ($-40\pm 18^{\circ}\text{F}\sim221\pm 27^{\circ}\text{F}$)
 - Voltage sensor: $1.9\pm 0.1\text{V}\sim3.9\pm 0.1\text{V}$

The security of the device is not compromised by altering the environmental conditions (e.g., placing the device outside of the stated operating temperature ranges or the operating voltages do not alter the security).

3.4 Configuration Settings

The security functions are an inherent part of the firmware functions. No security sensitive configuration settings are necessary to be adjusted by the end user in order to meet security requirements.

3.5 Periodic Inspection and Maintenance

Check the device once a day, the actual frequency can be adjusted according to the specific situation. Users should check the following items.

- Missing or damaged screws
- Incorrect or redundant keyboard overlays
- Holes that should not exist in the housing of the device
- External wires around the device
- Missing or unmatched manufacturer barcode label

- Any suspicious objects in or around the IC card slot, refer to the below picture for normal state.



- Any suspicious objects in and around the MSR slot, refer to the below picture for normal state.



- Tamper message on the device, refer to “4.1 Tamper Response”

If any anomalies are found indicating the device may have been opened or tampered, stop using the device immediately and contact the supplier to explain any concern.

3.6 Roles and Responsibilities

The customers of PAX are referred to as the Acquirer or Value Added Resellers (VAR). PAX also refers to VAR directly as the Acquirer. PAX sells devices and provides technical support as well as maintenance to the Acquirer. The Acquirer sells the devices to the end users and provides services to their end users. PAX, the Acquirer and the End Users play different roles in the operation of the device. The table below shows the different roles and operations:

Table 1 Different roles and responsibilities

	Role	Responsibilities
VAR/Acquirer/Merchant	Administrator	1. Organize the third party to develop application program; 2. Download application, and request certificate from vendor.
End User	Operator	Perform transaction
PAX	Maintainer	1. Sign customer public key 2. Repair device and unlock the device if tampered

3.7 Passwords and Certificates

No security related default value exists.

The device does not come with any certificates for testing purposes after being manufactured.

3.8 Decommissioning

Sensitive data and keys must be erased before the device is decommissioned and removed from service permanently. This can be done by rendering the device into tampered status, such as by disassembling the device. In the case of temporary removal (e.g., maintenance personnel unbind the server, etc.), it is not necessary to remove the keys.

4 Hardware Security

4.1 Tamper Response

In the tamper event, the device will turn into the locked status and only the tamper message will be displayed on the screen without any other tamper warning, as shown in the figure below. No further secure functions can be performed on the device.




Figure 5 Tamper Prompt

If the device is in tampered status, the user must immediately contact the device maintenance or authorized service center and remove the device from service.

4.2 Privacy Shield

The device is designed to be used as a handheld device, therefore the device does not contain a privacy shield. The device is compliant with the characteristics of a handheld device as required by Appendix A.2 of the DTR.

It is recommended to enter the PIN in the following ways:

- Make sure the cardholder holds the device on hand during PIN entry.
- Make sure the cardholder keeps a distance from others at the check stand.
- Make sure no video camera is aimed towards the keypad.
- Remind the cardholder to examine if anyone can see the keypad before PIN entry.

The following table shows the combination of methods that could be used when installing the terminal to protect the cardholder's PIN during PIN entry.

Table 2 Combination of methods to protect PIN entry

Methods	Observation Corridors				
	Cashier	Customers in Queue	Customers Elsewhere	On-Site Cameras	Remote Cameras
with stand	No action needed.	Customer positions terminal	No action needed.	Out of sight of the camera	Out of sight of the camera
without stand	Block the view of cashier by body	Block the view of other customers by body	Block the view of other customers by body	Out of sight of the camera	Out of sight of the camera
Customer Instruction	Remind the customer to shield PIN	Keep a distance	Keep a distance	Out of sight of the camera	Out of sight of the camera

5 Software Security

Software security includes self-test, patching/updating and software signing. The device does not allow unauthorized or unnecessary functions.

5.1 Self-test

The device employs the start-up self-test and periodic self-test to confirm the legality of the firmware and software, as well as to reinitialize the memory. The self-test includes:

- Check the integrity and authenticity of the firmware
- Check the integrity and authenticity of the application

If any of the above checks fail, the device will be disabled in a secure manner. In this case, please contact the supplier's service center.

The device provides two periodic restart schemes: 24-hour restart scheme and scheduled restart scheme.

5.1.1 24-hour Restart Scheme

The device performs a self-test every time it is turned on. If the device has been running for 24 hours since being turned on, the device will restart, unless there is a delay due to business reasons. The default maximum delay for the device does not exceed 48 hours.

5.1.2 Scheduled Restart Scheme

The device also provides a scheduled restart scheme as an option for users.

The user can schedule a fixed time for the restart, in which case the device will restart at the scheduled time every day, unless there is a delay due to business reasons. The default maximum delay for the device does not exceed 48 hours.

5.2 Patching and Updating

Update and/or patch to the firmware, software and configuration parameters can be installed into the device. The device supports local update through USB, U-DISK and SD card. The device supports remote update through Wi-Fi , Ethernet or Cellular.

Any security related update and/or patch loaded into PAX terminals must be signed. The signature will be verified by the firmware. If the signature of the update and/or patch cannot be

authenticated, the update and/or patch will be rejected and not be installed.

For the secure operation of the device, it is recommended to use the latest versions of the released firmware and software.

5.3 Software Signing/Authentication

The User Key Management Machine (uKMM) provided by PAX is used to sign the user application. The uKMM administrators perform the user private key loading operation and the signing process under dual control and split knowledge.

Only the application codes that have been authorized for release should be signed.

The application is verified by the firmware before it is loaded and executed. If the verification fails, the application cannot be loaded into the device and executed. The signature and verification mechanism ensure the authenticity and integrity of the application that is loaded into the device.

The payment application update uses SHA-256 in combination with RSA 4096 bits for authentication and signature verification.

The third-party application update uses at least SHA-256 in combination with at least RSA 2048 bits for authentication and signature verification.

5.4 Software Development Guidance

PAX provides a software-programming guide for developers to develop applications compliant with PCI security requirement. Please refer to [4] when developing SRED function and OP function.

The device does not allow unauthorized or unnecessary functions.

5.5 Account Data Protection

The device always provides SRED functionality and does not support the disablement (turning off) of SRED functionality.

For the SRED module, account data can be encrypted by TDES/AES/RSA encryption. The device supports account data protection by using format-preserving encryption (FPE) with AES FF1 mode.

The firmware of the device does not support the pass-through of clear-text account data by using techniques such as whitelisting. For more details, please refer to [4].

The third-party applications are prevented from accessing cleartext account data.

6 Key Management

6.1 Algorithms Supported

The device supports the following algorithms:

- TDES (112 bits/168 bits)
- AES (128 bits/192 bits/256 bits)
- RSA (2048 bits / 4096 bits)
- SHA (256 bits)
- ECC (in support with NIST P-256, P-384 and P-521)

6.2 Key Management Methods

The device supports the following key management methods:

- Master/Session Key
 - This method uses a hierarchy of Master Key and Session Key.
- DUKPT
 - This method uses a unique key for each transaction.

Use of the device with different key-management systems will invalidate the PCI PTS POI approval of the device.

Table 3 Supported Key Management Methods

Purpose	Supported Key Management
Key Management – PIN encryption	TDES - MK/SK
	TDES - DUKPT
	AES - MK/SK
	AES - DUKPT
Key Management – Account Data Encryption	TDES - MK/SK
	TDES - DUKPT
	AES - MK/SK
	AES - DUKPT
	Format-Preserving Encryption
	RSA

6.3 Key Table

Table 4 RSA public key

Key name	Usage	Algorithm	Size (bits)
US_PUK (PAX_US_PUK/C_US_PUK)	Public key for application authentication	RSA	4096
Trans-Armor public key	Account data encryption	RSA	2048
CA_PUK	Used for verification of the device, LKI or RKI certificates.	RSA	2048
DA_PVK / DA_PUK	Used for device authentication by RKI server.	RSA	2048
DE_PVK / DE_PUK	Used to protect sensitive information during remote key injection.	RSA	2048
RKIAK_PUK	Used for authentication between RKI server and the device during remote key injection procedure.	RSA	2048

Table 5 Symmetric Key

Key name	Purpose/Usage	Algorithm	Size(bytes)
Master Key (TMK)	To load encrypted session keys	TDES	16/24
		AES	16/24/32
PIN Key (TPK)	PIN encryption for PINBLOCK format 0,1,3 under TDES algorithm; PIN encryption for PINBLOCK format 4 under AES algorithm.	TDES	16/24
		AES	16/24/32
MAC Key (TAK)	MAC Calculation	TDES	16/24
		AES	16/24/32
Account Data Encryption Key (TCHDK)	Account Data Encryption	TDES	24
		AES	16/24/32
Data Key (TDK)	Arbitrary Data Encryption	TDES	16/24
		AES	16/24/32
DUKPT Initial Key (TIK)	DUKPT Initial Key, used to generate DUKPT future keys.	TDES	16
		AES	16/24/32
DUKPT Future Key	DUKPT Encryption Keys, used for PIN encryption, Account data encryption, MAC calculation and arbitrary data encryption.	TDES	16
		AES	16/24/32
FPE Key	Account Data Encryption under Voltage FPE scheme	AES	16

6.4 Key Loading

The terminal supports the following key loading methods:

- Clear-text key injection.
- Symmetric encrypted keys, remote asymmetric key loading.
- Local asymmetric key loading.

The terminal supports clear-text key injection by using a key loader tool under dual control and split knowledge in a secure environment.

6.5 Key Replacement

Whenever it is known or suspected that a key has been compromised, and whenever it is considered feasible to determine the timing of the key using the exhaustive method, the key must be deleted or replaced with a new one.

7 Communications and Security Protocols

The device supports the communication methods and protocols listed below. Use of any method not listed here invalidates the PCI PTS POI approval of the device.

7.1 Communication Interfaces

The following communication interfaces are available in the device:

- Cellular (including SIM card slot and eSIM card port, supporting 2G/3G/4G)
- Wi-Fi
- Bluetooth BR/EDR/HS, BLE and Beacons
- GPS
- USB and USB-to-serial and USB-to-Ethernet

7.2 Communication Protocols and Services

The following protocols and services are supported for TCP/IP communications by the device:

- IP (IPv4, IPv6)
- ICMP, TCP, UDP
- PPP, ARP
- DHCP client, DNS client
- TLS (TLSv1.2 and TLSv1.3)
- VPN
- HTTP/HTTPS
- SOCKS
- NTP
- OCSP
- SSH, SFTP
- WS/WSS
- MQTT/MQTTS

About the details, please refer to [4] for more information.

7.3 Bluetooth Security Guidance

The terminal supports Bluetooth secure communications:

- BTv5.0 for BR/EDR/HS in Security Mode 4 Level 4;
- BTv5.0 for BLE in Security Mode 1 Level 4;
- Just works cannot be used at any time.

In addition, where the device communicates with Bluetooth BR/EDR/HS 2.1 through 4.0 peripheral devices, it falls back to Security Mode 4 Level 3.

The terminal supports transmit only BLE Beacons (e.g., iBeacon, EddyStone). The use of BLE Beacons is restricted:

- 1) Over-the-Air provisioning of beacons is not supported.
- 2) Beacons can only be used in transmit mode and must not be used to transmit sensitive data.
- 3) Beacons cannot be configured in connectable mode.
- 4) Beacons send a universally unique identifier and several bytes that can be used to determine the device's physical location or track customers.

Appendix

Acronyms

Acronyms	Description
PIN	Personal Identification Number
RSA	Rivest Shamir Adelman Algorithm
SHA	Secure Hash Algorithm
TDES	Triple Data Encryption Standard
AES	Advanced Encryption Standard
DUKPT	Derived Unique Key per Transaction

References

- [1] ANS X9.24-1, Retail Financial Services Symmetric Key Management Part 1: Using Symmetric Techniques
- [2] ANS X9.24-2, Retail Financial Services Symmetric Key Management Part 2: Using Asymmetric Techniques for the Distribution of Symmetric Keys
- [3] PAX White Paper.pdf
- [4] Secure Application Development Guide.pdf